

GRZAŁKA RUROWA ETG-F-T
LISTA PARAMETRÓW STANDARDOWYCH

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	1,5	[V]	[mm]
18FT-500	*osłona Ø51 DN50/80/100/150 PN16 DIN 2527	1050	230	500
18FT-600		1300	230	600
18FT-700		1500	230/3x400	700
18FT-800		1750	3x400	800
18FT-900		2000	3x400	900
18FT-1000		2250	3x400	1000
18FT-1100		2500	3x400	1100
18FT-1200		2700	3x400	1200
18FT-1400		3200	3x400	1400
18FT-1600		3500	3x400	1600
18FT-1800		4000	3x400	1800
18FT-2000		4500	3x400	2000

*materiał osłony: 1.4301

* inne parametry na zapytanie

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	3,0	[V]	[mm]
19FT-500	*osłona Ø51 DN50/80/100/150 PN16 DIN 2527	2100	230	500
19FT-600		2500	230	600
19FT-700		3000	230/3x400	700
19FT-800		3450	3x400	800
19FT-900		3850	3x400	900
19FT-1000		4300	3x400	1000
19FT-1100		4500	3x400	1100
19FT-1200		5000	3x400	1200
19FT-1400		6000	3x400	1400
19FT-1600		6900	3x400	1600
19FT-1800		7800	3x400	1800
19FT-2000		9000	3x400	2000