

## GRZAŁKA RUROWA ETG-P

### LISTA PARAMETRÓW STANDARDOWYCH

ETG-P / G1 ½"				
---------------	--	--	--	--

	Gwint	Moc przy [W/cm <sup>2</sup> ]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	1,5	[V]	[mm]
03P-300	G1 ½", * osłona Ø40	450	230	300
03P-400		650	230	400
03P-500		800	230	500
03P-600		1000	230	600
03P-700		1200	230/3x400	700
03P-800		1400	230/3x400	800
03P-900		1600	230/3x400	900
03P-1000		1750	230/3x400	1000
03P-1100		1950	230/3x400	1100
03P-1200		2150	230/3x400	1200
03P-1400		2500	3x400	1400
03P-1600		2900	3x400	1600
03P-1800		3250	3x400	1800
03P-2000		3650	3x400	2000

ETG-P / G 1 ½"				
----------------	--	--	--	--

	Gwint	Moc przy [W/cm <sup>2</sup> ]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	3,0	[V]	[mm]
04P-300	G1 ½", * osłona Ø40	900	230	300
04P-400		1300	230	400
04P-500		1650	230	500
04P-600		2050	230	600
04P-700		2400	230/3x400	700
04P-800		2800	230/3x400	800
04P-900		3200	230/3x400	900
04P-1000		3550	3x400	1000
04P-1100		3950	3x400	1100
04P-1200		4300	3x400	1200
04P-1400		5050	3x400	1400
04P-1600		5800	3x400	1600
04P-1800		6550	3x400	1800
04P-2000		7300	3x400	2000

\* materiał osłony: 1.4301

\* inne parametry na zapytanie

