

LISTA PARAMETRÓW STANDARDOWYCH

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	1,5	[V]	[mm]
18FT-500	* osłona Ø51 DN50/80/100/150 PN16 DIN 2527	1000	230	500
18FT-600		1200	230	600
18FT-700		1400	230/3x400	700
18FT-800		1600	3x400	800
18FT-900		1800	3x400	900
18FT-1000		2000	3x400	1000
18FT-1100		2200	3x400	1100
18FT-1200		2400	3x400	1200
18FT-1400		2800	3x400	1400
18FT-1600		3200	3x400	1600
18FT-1800		3700	3x400	1800
18FT-2000		4000	3x400	2000

*materiał osłony: 1.4301

* inne parametry na zapytanie

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	3,0	[V]	[mm]
19FT-500	* osłona Ø51 DN50/80/100/150 PN16 DIN 2527	1900	230	500
19FT-600		2400	230	600
19FT-700		2800	230/3x400	700
19FT-800		3200	3x400	800
19FT-900		3700	3x400	900
19FT-1000		4100	3x400	1000
19FT-1100		4300	3x400	1100
19FT-1200		4700	3x400	1200
19FT-1400		5500	3x400	1400
19FT-1600		6400	3x400	1600
19FT-1800		7400	3x400	1800
19FT-2000		8100	3x400	2000