

LISTA PARAMETRÓW STANDARDOWYCH

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	1,5	[V]	[mm]
16F-500	* osłona Ø51 DN40/50/80 PN16 DIN 2527	1000	230	500
16F-600		1200	230	600
16F-700		1400	230/3x400	700
16F-800		1600	3x400	800
16F-900		1800	3x400	900
16F-1000		2000	3x400	1000
16F-1100		2200	3x400	1100
16F-1200		2400	3x400	1200
16F-1400		2800	3x400	1400
16F-1600		3200	3x400	1600
16F-1800		3700	3x400	1800
16F-2000		4000	3x400	2000

*materiał osłony: 1.4301

* inne parametry na zapytanie

ETG-F				
	Kołnierz	Moc przy [W/cm ²]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	DN	3,0	[V]	[mm]
17F-500	* osłona Ø51 DN40/50/80 PN16 DIN 2527	1900	230	500
17F-600		2400	230	600
17F-700		2800	230/3x400	700
17F-800		3200	3x400	800
17F-900		3700	3x400	900
17F-1000		4100	3x400	1000
17F-1100		4300	3x400	1100
17F-1200		4700	3x400	1200
17F-1400		5500	3x400	1400
17F-1600		6400	3x400	1600
17F-1800		7400	3x400	1800
17F-2000		8100	3x400	2000