

LISTA PARAMETRÓW STANDARDOWYCH

ETG-M / G1 ½"				
	Gwint	Moc przy [W/cm2]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	0,8	[V]	[mm]
09M-300	G1 ½", osłona Ø40	250	230	300
09M-400		300	230	400
09M-500		400	230	500
09M-600		500	230	600
09M-700		600	230/400	700
09M-800		700	230/400	800
09M-900		800	230/400	900
09M-1000		900	230/400	1000
09M-1100		1000	230/400	1100
09M-1200		1100	230/400	1200
09M-1400		1200	230/400	1400
09M-1600		1400	230/3x400	1600
09M-1800		1600	230/3x400	1800
09M-2000		1800	230/3x400	2000

ETG-M / G1 ½"				
	Gwint	Moc przy [W/cm2]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	1,5	[V]	[mm]
10M-300	G1 ½", osłona Ø40	450	230	300
10M-400		600	230	400
10M-500		700	230	500
10M-600		950	230	600
10M-700		1100	230/400	700
10M-800		1250	230/400	800
10M-900		1400	230/400	900
10M-1000		1600	230/3x400	1000
10M-1100		1700	230/3x400	1100
10M-1200		1900	230/3x400	1200
10M-1400		2200	3x400	1400
10M-1600		2500	3x400	1600
10M-1800		2900	3x400	1800
10M-2000		3300	3x400	2000

* inne parametry na zapytanie