

LISTA PARAMETRÓW STANDARDOWYCH

ETG-P / G1 ½"				
	Gwint	Moc przy [W/cm2]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	1,5	[V]	[mm]
03P-300	G1 ½", *osłona Ø40	450	230	300
03P-400		600	230	400
03P-500		700	230	500
03P-600		950	230	600
03P-700		1100	230/400	700
03P-800		1250	230/400	800
03P-900		1400	230/400	900
03P-1000		1600	230/3x400	1000
03P-1100		1700	230/3x400	1100
03P-1200		1900	230/3x400	1200
03P-1400		2200	3x400	1400
03P-1600		2500	3x400	1600
03P-1800		2900	3x400	1800
03P-2000		3300	3x400	2000

*materiał osłony: 1.4301

* inne parametry na zapytanie

ETG-P / G 1 ½"				
	Gwint	Moc przy [W/cm2]	Napięcie	Długość zanurzeniowa [L]
Nr. katalogowy	[G"]	3,0	[V]	[mm]
04P-300	G1 ½", *osłona Ø40	800	230	300
04P-400		1100	230	400
04P-500		1500	230	500
04P-600		1800	230	600
04P-700		2100	230/3x400	700
04P-800		2500	230/3x400	800
04P-900		2900	230/3x400	900
04P-1000		3200	3x400	1000
04P-1100		3500	3x400	1100
04P-1200		3700	3x400	1200
04P-1400		4200	3x400	1400
04P-1600		4900	3x400	1600
04P-1800		5500	3x400	1800
04P-2000		6100	3x400	2000