

LISTA PARAMETRÓW STANDARDOWYCH

ETG-P / G2 ½"

| | Gwint | Moc przy [W/cm2] | Napięcie | Długość zanurzeniowa [L] |
|----------------|-----------------------|------------------|----------|--------------------------|
| Nr. katalogowy | [G"] | 1,5 | [V] | [mm] |
| 07P-400 | G2 ½", *ośstona Ø63,5 | 900 | 3x400 | 400 |
| 07P-500 | | 1200 | | 500 |
| 07P-600 | | 1450 | | 600 |
| 07P-700 | | 1700 | | 700 |
| 07P-800 | | 1950 | | 800 |
| 07P-900 | | 2250 | | 900 |
| 07P-1000 | | 2400 | | 1000 |
| 07P-1100 | | 2750 | | 1100 |
| 07P-1200 | | 3000 | | 1200 |
| 07P-1400 | | 3500 | | 1400 |
| 07P-1600 | | 4000 | | 1600 |
| 07P-1800 | | 4500 | | 1800 |
| 07P-2000 | | 5100 | | 2000 |

*materiał osłony: 1.4301

* inne parametry na zapytanie

ETG-P / G2 ½"

| | Gwint | Moc przy [W/cm2] | Napięcie | Długość zanurzeniowa [L] |
|----------------|-----------------------|------------------|----------|--------------------------|
| Nr. katalogowy | [G"] | 3,0 | [V] | [mm] |
| 08P-400 | G2 ½", *ośstona Ø63,5 | 1700 | 3x400 | 400 |
| 08P-500 | | 2150 | | 500 |
| 08P-600 | | 2500 | | 600 |
| 08P-700 | | 3000 | | 700 |
| 08P-800 | | 3500 | | 800 |
| 08P-900 | | 4000 | | 900 |
| 08P-1000 | | 4500 | | 1000 |
| 08P-1100 | | 5000 | | 1100 |
| 08P-1200 | | 5600 | | 1200 |
| 08P-1400 | | 6500 | | 1400 |
| 08P-1600 | | 7550 | | 1600 |
| 08P-1800 | | 8600 | | 1800 |
| 08P-2000 | | 9500 | | 2000 |