

LISTA PARAMETRÓW STANDARDOWYCH

| ETG-P / G2" | | | | |
|----------------|------------------|------------------|-----------|--------------------------|
| | Gwint | Moc przy [W/cm2] | Napięcie | Długość zanurzeniowa [L] |
| Nr. katalogowy | [G"] | 1,5 | [V] | [mm] |
| 05P-300 | G2", *osłona Ø51 | 550 | 230 | 300 |
| 05P-400 | | 750 | 230 | 400 |
| 05P-500 | | 1000 | 230 | 500 |
| 05P-600 | | 1200 | 230 | 600 |
| 05P-700 | | 1400 | 230/3x400 | 700 |
| 05P-800 | | 1600 | 230/3x400 | 800 |
| 05P-900 | | 1800 | 230/3x400 | 900 |
| 05P-1000 | | 2000 | 3x400 | 1000 |
| 05P-1100 | | 2200 | 3x400 | 1100 |
| 05P-1200 | | 2400 | 3x400 | 1200 |
| 05P-1400 | | 2800 | 3x400 | 1400 |
| 05P-1600 | | 3200 | 3x400 | 1600 |
| 05P-1800 | | 3700 | 3x400 | 1800 |
| 05P-2000 | | 4000 | 3x400 | 2000 |

*materiał osłony: 1.4301

* inne parametry na zapytanie

| ETG-P / G2" | | | | |
|----------------|------------------|------------------|-----------|--------------------------|
| | Gwint | Moc przy [W/cm2] | Napięcie | Długość zanurzeniowa [L] |
| Nr. katalogowy | [G"] | 3,0 | [V] | [mm] |
| 06P-300 | G2", *osłona Ø51 | 1100 | 230 | 300 |
| 06P-400 | | 1400 | 230 | 400 |
| 06P-500 | | 1900 | 230 | 500 |
| 06P-600 | | 2400 | 230 | 600 |
| 06P-700 | | 2800 | 230/3x400 | 700 |
| 06P-800 | | 3200 | 3x400 | 800 |
| 06P-900 | | 3700 | 3x400 | 900 |
| 06P-1000 | | 4100 | 3x400 | 1000 |
| 06P-1100 | | 4300 | 3x400 | 1100 |
| 06P-1200 | | 4700 | 3x400 | 1200 |
| 06P-1400 | | 5500 | 3x400 | 1400 |
| 06P-1600 | | 6400 | 3x400 | 1600 |
| 06P-1800 | | 7400 | 3x400 | 1800 |
| 06P-2000 | | 8100 | 3x400 | 2000 |