

LIST OF STANDARD PARAMETERS

ETG-M / G2"				
	Thread	Power [W/cm2]	Voltage	Immersion length [L]
Catalog Number	[G"]	0,8	[V]	[mm]
11M-300	G2", cover Ø53	300	230	300
11M-400		450	230	400
11M-500		550	230	500
11M-600		700	230	600
11M-700		850	230/400	700
11M-800		950	230/400	800
11M-900		1100	230/3x400	900
11M-1000		1250	230/3x400	1000
11M-1100		1350	230/3x400	1100
11M-1200		1500	230/3x400	1200
11M-1400		1750	230/3x400	1400
11M-1600		2050	230/3x400	1600
11M-1800		2300	3x400	1800
11M-2000		2550	3x400	2000

ETG-M / G2"				
	Thread	Power [W/cm2]	Voltage	Immersion length [L]
Catalog Number	[G"]	1,5	[V]	[mm]
12M-300	G2", cover Ø53	500	230	300
12M-400		800	230	400
12M-500		1000	230	500
12M-600		1300	230	600
12M-700		1500	230/3x400	700
12M-800		1700	230/3x400	800
12M-900		2000	230/3x400	900
12M-1000		2200	3x400	1000
12M-1100		2400	3x400	1100
12M-1200		2600	3x400	1200
12M-1400		3000	3x400	1400
12M-1600		3500	3x400	1600
12M-1800		4000	3x400	1800
12M-2000		4400	3x400	2000

* others on request