

LIST OF STANDARD PARAMETERS

ETG-P / G2"				
	Thread	Power [W/cm2]	Voltage	Immersion length [L]
Catalog Number	[G"]	1,5	[V]	[mm]
05P-300	G2" , *cover Ø51	550	230	300
05P-400		750	230	400
05P-500		1000	230	500
05P-600		1200	230	600
05P-700		1400	230/3x400	700
05P-800		1600	230/3x400	800
05P-900		1800	230/3x400	900
05P-1000		2000	3x400	1000
05P-1100		2200	3x400	1100
05P-1200		2400	3x400	1200
05P-1400		2800	3x400	1400
05P-1600		3200	3x400	1600
05P-1800		3700	3x400	1800
05P-2000		4000	3x400	2000

*material of casing: 1.4301

* others on request

ETG-P / G2"				
	Thread	Power [W/cm2]	Voltage	Immersion length [L]
Catalog Number	[G"]	3,0	[V]	[mm]
06P-300	G2" , *cover Ø51	1100	230	300
06P-400		1400	230	400
06P-500		1900	230	500
06P-600		2400	230	600
06P-700		2800	230/3x400	700
06P-800		3200	3x400	800
06P-900		3700	3x400	900
06P-1000		4100	3x400	1000
06P-1100		4300	3x400	1100
06P-1200		4700	3x400	1200
06P-1400		5500	3x400	1400
06P-1600		6400	3x400	1600
06P-1800		7400	3x400	1800
06P-2000		8100	3x400	2000